



DRYWALL PRIMER SEALER

Dulux Trade Drywall Primer Sealer is a high quality, water-based wall paint primer sealer developed to help even out surface porosity on drywall and promote a good finish and high opacity. It is suitable for all interior drywall and ceiling surfaces and binds and seals powdery surfaces.

KEY BENEFITS

- Evens Drywall Porosity
- Binds & Seals Powdery Surfaces
- Promotes a Good Finish & High Opacity

PRODUCT INFORMATION

Typical Use

Suitable for all interior drywall and ceiling surfaces

Pack Size

10L.

Colour Range

White only

Composition (nominal)

Pigment: Lightfast Pigments.

Binder: Acrylic Copolymer Emulsion.

Solvent: Water.

Volume Solids

White: 27% (nominal).

SURFACE PREPARATION

Surfaces must be clean and dry before painting.

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Any surface defects should be filled with the appropriated **Polycell Trade Polyfilla**.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Use **Dulux Trade** Drywall Primer Sealer on new or bare surfaces. The normal finishing process in 2 coats of a recommended **Dulux Trade** emulsion.

APPLICATION METHOD

Apply by brush, roller or spray.

Practical Coverage

A guide to the practical coverage which can be achieved is up to 15m² per litre.

Thinning

Thinning is not normally required.

Spray Recommendations

Conventional Spray: Satisfactory through most equipment.

Airless Spray: A typical set up for airless spray application would be a minimum working pressure on paint of 133 bars (2000lb/sq in) with a spray tip size of 0.38mm (15 thou) and a spray tip angle of 65°.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 2-4 hours.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/pp.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.



DRYWALL PRIMER SEALER

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010). This product contains max. 1g/l VOC. VOC Content: Minimal (0-0.29%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 548) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At **Dulux Trade**, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at duluxtrade.co.uk/pp