



TECHNICAL DATA SHEET

Rocktop is an extra tough clearcoat that seals, protects and enhances most surfaces. Rocktop has been expertly formulated for even the most high traffic areas in the home. Clearcoat is water-based so won't yellow, and dries clear. Available in Matt, Satin and Gloss finishes.

USES

Smith & Rodger Rocktop Clearcoat has been expertly formulated for use on a multitude of surfaces. Ideal for use on all interior woodwork including high traffic wooden floors, kitchen worktops, furniture, doors and trim. Perfect for sealing brick and stone, vinyl floors, painted walls (such as in bathrooms), and other surfaces such as cork, tile or wallpaper. Can also be used as an additive for emulsion paints to make them more hardwearing.

PREPARATION

Ensure the surface you are going to coat is clean, dry and free from dust, dirt and excessive oil, grease, wax, wallpaper adhesive or loose and flaky paint that may interfere with application.

Special precautions should be taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead.

When applying to wood - Sand wood to remove any loose wood fibres and remove any remaining residues of previous coatings. Avoid the inhalation of dust and wear a suitable face mask if dry sanding.

When applying to coated surface – sand back slightly to provide adhesion, if the coating looks to be in good condition. If the coating is in poor condition and will affect the appearance of the finished clearcoat, it is advisable to remove the previous coating completely before application.

APPLICATION

Ensure room conditions are warm, dry and well ventilated.

For best results, apply when air temperature is over 13° and relative humidity is less than 65%. Shake or stir before applying by brush or roller. Apply 3 coats, or more if high traffic is expected. Allow the previous coat to dry thoroughly, for at least 3 hours before applying the next coat. A light sand between coats will improve appearance. Keep container closed and store upright when not in use. If applying to floors, avoid heavy use for 72 hours after the final coat and do not place rugs on floors until fully cured.

DRYING TIME

Touch Dry in 30 minutes. Recoat after 2 hours. Full cure in 7 days

COVERAGE

10 Sq. m. per Litre. Approximately 25 square metres per 2.5L can. Note that coverage will vary between surfaces, as bare wood is more absorbent than previously coated wood.

CLEAN UP

Clean brushes and equipment with water. Wash any splashes to skin or fabric immediately.

Disposal: refer to local authorities advice on disposal. Do not empty into drains or waterways.

HEALTH, SAFETY & THE ENVIRONMENT

KEEP OUT OF REACH OF CHILDREN. Wear suitable protective clothing and gloves. Use only in well ventilated areas. In case of contact with eyes, rinse immediately with water and seek medical advice. If swallowed seek medical advice immediately and show this container. VOC content:

Manufactured in the UK by:

Smith & Rodger

34 Elliot St,

Glasgow G3 8EA

For further product information or customer service enquiries please visit www.smithandrodger.co.uk

Or contact us on: Tel: [0141 248 6341](tel:01412486341) E info@smithandrodger.co.uk