

940 -1

ARTISAN

SPECIAL EFFECTS PAINTS

CHALK WASH

TYPE OF MATERIAL	Chalkwash is an interior water based paint which is a translucent finish that can achieve a variety of possible paint effects during application. Applied by a Brush or other methods.
USES	An internal decorative effect paint to imitate WASH paints and their effects by applying over a contrasting base colour of Chalky Emulsion.
COLOURS AVAILABLE	4 colours – see website.
FINISH	Translucent patterned effect.
NUMBER OF COMPONENTS	One component / Use over a contrasting colour to create the effect.
METHOD OF APPLICATION	Brush, effects brush, Rag Roll , Bag , Clouding.
AVAILABLE PACKS	750ml
SHEEN LEVEL	A low sheen Matt translucent.
PRACTICAL COVERAGE PER LITRE	7.5sqm / 750ML
FLASH POINT	N/A Water based.
DRYING TIMES: SURFACE RECOAT	4 Hours Not applicable
PREPARATION	Remove loose or flaking paint, fill cracks or holes with filler and sand smooth. Abrade any silk, satin or glossy surfaces before painting over. Treat any mould with scouring pad and bleach solution (1part to 3 with water).leave on surface for 15minutes then wash with clean water and dry. Surfaces must be clean and dry and free from grease oil or dirt or flaking coatings before painting. New dry plaster, or porous surfaces should be primed with a coat of Craig & Rose Primer Undercoat or other suitable primer.

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

940 -1

ARTISAN

SPECIAL EFFECTS PAINTS

CHALK WASH

APPLICATION INSTRUCTIONS	<p>Always apply a contrasting colour of Matt emulsion before the Chalkwash, we recommend 1829 Chalky emulsion and there are suggestions for contrasting colours on the website. Apply in blocks of around 1m square then create the pattern required by using different types of brush at different angles or use a Rag rolling or bagging technique. Blend in carefully further blocks taking care at overlaps to cover the whole wall. If two people are available then one can apply the wash and the other come behind and create the pattern.</p> <p>Do Not apply a second coat as this may hide the translucent effect.</p>
RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS	<p>Ensure the emulsion basecoat has dried for 4 hrs before applying Chalkwash. Do not apply in temperatures near freezing as this will seriously slow down the drying and may destroy the structure of the paint. Store in a frost-free place and do not allow the paint to freeze. Do not apply to highly absorbant or highly shiny surfaces.</p>
CLEANING	<p>Remove as much paint as possible from equipment before cleaning with water. Clean hands with warm soapy water.</p>
SAFETY PRECAUTIONS	<p>Ensure good ventilation during application and drying. After contact with skin, wash immediately with plenty of soap and water. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. See can label for full instructions.</p> <p>Safety Data Sheets are available on request.</p>
VOC CONTENT (VOLATILE ORGANIC COMPOUNDS)	<p>2004/42 EU Limit value for this product (Cat A/I : 200g/L)</p> <p>This product contains Max : 150g/L VOC.</p>
DISPOSAL & ENVIRONMENT	<p>Please dispose of unused paint and container responsibly. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of paint.</p>

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.