

## DESCRIPTION

Classic Matt Woodstain has been specially formulated to provide an easy maintenance protective, microporous, low sheen finish for above ground exterior timber such as rough sawn, barge boards, cladding and decking. This special formulation resists cracking, blistering and peeling.

## AVAILABLE IN

750ml, 2.5 litre and 5 litre sizes.

## COLOUR RANGE

Clear; Light Oak; Jacobean Oak; Redwood; Mahogany; Ebony; Medium Oak; Walnut; Pine; Antique Pine; Rosewood; and Teak.

A Range of colours available in 2.5 litre and 5 litre only via the Johnstone's CMS2010 Tinting System.

## RECOMMENDED USES




Suitable for interior & exterior use.

## TYPES OF SUBSTRATE

Rough sawn timber, barge boards, cladding, garden furniture, decking.

## COVERAGE



Approximately 15 square metres per litre depending on the nature and porosity of the surface being stained.

## DRYING TIME



Recoat after 16–24 hours.  
Allow longer in adverse conditions.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.

**STORE AWAY FROM HEAT AND FLAME.**

## CLEANER

White Spirit.

## VOC CONTENT

HIGH VOC CONTENT 25-50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/e): 400g/l (2010). This product contains max 400g/l VOC.

## PREPARATION

Ensure all surfaces to be stained are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Treat any mould or lichen with Sterilisation Wash as directed. Remove any flaking or cracked varnish and fill any cracks or joints with filler. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Previously painted wood should have all traces of previous treatments removed using a Paint & Varnish Stripper. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com)

## APPLICATION



Stir Matt Woodstain thoroughly before use. Apply two or more coats of varnish evenly, by brush along the wood grain as required, paying particular attention to the end grain. New untreated softwood should first be treated with a suitable clear preserver. On bare or new wood, apply at least two coats of Matt Woodstain to give maximum durability. Sand down lightly between coats. **PLEASE NOTE:** The final colour will depend on the original colour of the wood and the number of coats applied.

## CLEANING



Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- **WARNING**
- Flammable liquid and vapour.
- Contains 2-butanone oxime and octhilonone (ISO). May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use solvent thinners or White Spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.