

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Article
Product name : 125/G139 - SUREGRIP (ALL COLOURS)
UFI : TD8P-V2N3-0004-CD6U
Product code : 10490
Product group : End product
Other means of identification : 125/G139/ ALL COLOURS

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Main use category : Consumer use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Supplier**

Coo-Var
Lockwood Street
Hull – East Yorkshire
England
T +44 (0)1482 328053
info@coo-var.co.uk

Distributor

Teal & Mackrill EU B.V.
Queens Towers
Delflandlaan 1
1062 EA Amsterdam
Netherlands
T +31 (0)208 004828
info@teamac.co.uk

1.4. Emergency telephone number

Emergency number : +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3 H226
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02



GHS07

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Signal word (CLP)	: Warning
Contains	: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, HYDROCARBONS, C9, AROMATICS
Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking. EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Calcium Magnesium Carbonate - Mic 0-0.5 substance with national workplace exposure limit(s) (GB)	CAS-No.: 16389-88-1 EC-No.: 240-440-2	$\geq 30 - < 50$	Not classified
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258-33	$\geq 10 - < 30$	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
Calcium Carbonate substance with a Community workplace exposure limit	CAS-No.: 1317-65-3 EC-No.: 215-279-6	$\geq 5 - < 10$	Not classified
Titanium Dioxide substance with national workplace exposure limit(s) (GB)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 REACH-no: 01-2119489379-17	$\geq 1 - < 5$	Not classified
HYDROCARBONS, C9, AROMATICS substance with national workplace exposure limit(s) (GB)	CAS-No.: 64742-95-6 EC-No.: 918-668-5 REACH-no: 01-2119455851-35	$\geq 1 - < 5$	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Yellow Iron Oxide substance with national workplace exposure limit(s) (GB)	CAS-No.: 51274-00-1 EC-No.: 257-098-5 REACH-no: 01-2119454754-33	$\geq 1 - < 5$	Not classified
Organoclay substance with national workplace exposure limit(s) (GB)	CAS-No.: 68953-58-2 EC-No.: 273-219-4	$\geq 1 - < 5$	Not classified
C.I. Pigment Yellow substance with national workplace exposure limit(s) (GB)	CAS-No.: 6358-31-2 EC-No.: 228-768-4	$\geq 1 - < 5$	Not classified
Red Iron Oxide substance with national workplace exposure limit(s) (GB)	CAS-No.: 1309-37-1	< 1	Not classified
Barium Sulphate substance with national workplace exposure limit(s) (GB)	CAS-No.: 7727-43-7 EC-No.: 231-784-4 REACH-no: 01-2119491274-35	< 1	Not classified
ETHANOL substance with national workplace exposure limit(s) (GB)	CAS-No.: 64-17-5 EC-No.: 200-578-6 REACH-no: 01-2119457610-43	< 1	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Dipropylene Glycol Methyl Ether substance with national workplace exposure limit(s) (GB)	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60	< 1	Not classified
2,6-Di-tert-butyl-p-cresol substance with national workplace exposure limit(s) (GB)	CAS-No.: 128-37-0 EC-No.: 204-881-4 REACH-no: 01-2119565113-46	< 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
METHANOL substance with national workplace exposure limit(s) (GB)	CAS-No.: 67-56-1 EC-No.: 200-659-6	< 1	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 (ATE=0.5 mg/l/4h) STOT SE 1, H370

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Seek medical attention immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes.
First-aid measures after ingestion	: Rinse mouth out with water. Do not induce vomiting. Drink plenty of water. Get medical advice/attention if you feel unwell.

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: dry chemical powder, alcohol-resistant foam, carbon dioxide (CO ₂).
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Heating may cause a fire or explosion.
Explosion hazard	: Vapours may form explosive mixture with air.

5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate area. Clean up any spills as soon as possible, using an absorbent material to collect it.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: See section 8 of the SDS for more information on personal protective equipment. Ventilate spillage area. Do not touch or walk on the spilled product.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Use personal protective equipment as required.
Emergency procedures	: Evacuate unnecessary personnel.

6.2. Environmental precautions

Prevent liquid from entering sewers, watercourses, underground or low areas.

6.3. Methods and material for containment and cleaning up

For containment	: Cover spill with non combustible material, e.g.: sand, earth, vermiculite.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Collect spillage. Large spills: scoop solid spill into closing containers. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	: Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Use personal protective equipment as required. Provide adequate ventilation to minimize dust and/or vapour concentrations.
Hygiene measures	: Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Store in tightly closed, leak-proof containers. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR.
Storage conditions	: Store in original container.
Incompatible products	: Oxidizing agent. Strong acids.
Storage area	: Store in a well-ventilated place.
Packaging materials	: Keep only in the original container in a cool, well-ventilated place away from combustible materials.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

METHANOL (67-56-1)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	266 mg/m ³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	333 mg/m ³
WEL STEL (OEL STEL) [ppm]	250 ppm

ETHANOL (64-17-5)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	1920 mg/m ³
WEL TWA (OEL TWA) [2]	1000 ppm

Organoclay (68953-58-2)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	10 mg/m ³ Inhalable dust
-----------------------	-------------------------------------

Calcium Carbonate (1317-65-3)

EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	10 mg/m ³ Inhalable Dust
----------	-------------------------------------

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Calcium Magnesium Carbonate - Mic 0-0.5 (16389-88-1)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	4 mg/m ³
Barium Sulphate (7727-43-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	10 mg/m ³ Inhalable dust
Red Iron Oxide (1309-37-1)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	4 mg/m ³ Respirable dust
WEL STEL (OEL STEL)	10 mg/m ³ as Iron
Yellow Iron Oxide (51274-00-1)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	5 mg/m ³ as Fe
WEL STEL (OEL STEL)	10 mg/m ³ as Fe
C.I. Pigment Yellow (6358-31-2)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	1.5 mg/m ³ Total Dust
Titanium Dioxide (13463-67-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	10 mg/m ³ Inhalable dust
Dipropylene Glycol Methyl Ether (34590-94-8)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	308 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
HYDROCARBONS, C9, AROMATICS (64742-95-6)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	19 mg/m ³ (8 hour)
WEL TWA (OEL TWA) [2]	100 ppm (8 hour)
2,6-Di-tert-butyl-p-cresol (128-37-0)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	10 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Personal, workplace, environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

8.2.2. Personal protection equipment

Personal protective equipment:

ISO 374-1. Safety glasses. Gloves. Wear respiratory protection.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Hand protection:

As a general principal, exposure should be managed by means other than the provision of protective gloves. Wear suitable gloves tested to EN374. Nitrile rubber gloves. Permeation time: minimum >480min long term exposure; material / thickness [mm]:

Other skin protection

Materials for protective clothing:

Use protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Combined respiratory protective device, for filtering gas and particles, with a specific canister

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Do not exceed the occupational exposure limits (OEL).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Various colours.
Appearance	: Viscous liquid. Coloured liquid.
Odour	: aromatic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: approx. 40°C Closed cup.

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not relevant.
Viscosity, kinematic	: > 20.5 mm ² /s
Viscosity, dynamic	: 6 – 8 P @ 25°C
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.3 – 1.6 @ 20°C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 350 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition. Avoid contact with hot surfaces.

10.5. Incompatible materials

Acids. Oxidizing agent.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
	pH: Not relevant.

HYDROCARBONS, C9, AROMATICS (64742-95-6)

pH	Not available.
----	----------------

Serious eye damage/irritation	: Not classified
	pH: Not relevant.

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HYDROCARBONS, C9, AROMATICS (64742-95-6)

pH	Not available.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified (classification not possible)

125/G139 - SUREGRIP (ALL COLOURS)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

METHANOL (67-56-1)

STOT-single exposure	Causes damage to organs.
----------------------	--------------------------

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

HYDROCARBONS, C9, AROMATICS (64742-95-6)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

125/G139 - SUREGRIP (ALL COLOURS)

Viscosity, kinematic	> 20,5 mm ² /s
----------------------	---------------------------

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Viscosity, kinematic	≤ 20,5 mm ² /s
----------------------	---------------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified
Not rapidly degradable

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

125/G139 - SUREGRIP (ALL COLOURS)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

12.4. Mobility in soil

No additional information available

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment

125/G139 - SUREGRIP (ALL COLOURS)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 01 02 - plastic packaging 15 01 04 - metallic packaging
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.

SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT (PAINT, Contains Low Aromatic White Spirit (38°C c.c.))	PAINT (PAINT, Contains Low Aromatic White Spirit (38°C c.c.))	Paint (PAINT, Contains Low Aromatic White Spirit (38°C c.c.))	PAINT (PAINT, Contains Low Aromatic White Spirit (38°C c.c.))	PAINT (PAINT, Contains Low Aromatic White Spirit (38°C c.c.))

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet


according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
Transport document description				
UN 1263 PAINT (PAINT, Contains Low Aromatic White Spirit (38°C c.c.)), 3, III, (D/E)	UN 1263 PAINT (PAINT, Contains Low Aromatic White Spirit (38°C c.c.)), 3, III	UN 1263 Paint (PAINT, Contains Low Aromatic White Spirit (38°C c.c.)), 3, III	UN 1263 PAINT (PAINT, Contains Low Aromatic White Spirit (38°C c.c.)), 3, III	UN 1263 PAINT (PAINT, Contains Low Aromatic White Spirit (38°C c.c.)), 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3Y

Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3, A72, A192
ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 163, 367, 650
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 163, 367, 650
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006, Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 and all its amendments and modifications. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 and all its amendments and modifications.

REACH Annex XVII (Restriction List)

Not applicable.

REACH Annex XIV (Authorisation List)

Not applicable.

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : < 350 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Handling and storage.

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes version of	Added	
	Revision date	Added	
	Indication of changes	Added	
8.2	Environmental exposure controls	Added	
15.2	Chemical safety assessment	Added	

Abbreviations and acronyms:

CAS-No.	Chemical Abstract Service number
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
PNEC	Predicted No-Effect Concentration
VOC	Volatile Organic Compounds

125/G139 - SUREGRIP (ALL COLOURS)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.