

WOODFILLER


A fast drying filler / stopper for use on softwoods or hardwoods. It has excellent adhesion and is ideal for small repairs and minor surface defects. Suitable for timber in interior and exterior situations to be overcoated with woodstains, varnishes or opaque finishes.

AVAILABILITY	
Colour range	White and 3 wood tones
Packaging	250mls
PROPERTIES	
Suitable Surfaces	Interior and exterior timber
Drying time @ 20°C/65% RH	Workable: 2 minutes Sandable: 30 minutes Coatable: 2 hours Note: Drying times are dependent upon absorption, type of substrate and drying conditions. At low temperatures and/ or conditions of high relative humidity, drying times will be extended.
Finish	Matt
Composition	Nitro-cellulose resin dispersed / dissolved in an organic solvent.
Volume solids	99%
Flash point	56°C (closed cup)
VOC content	Not applicable
Limitations	Do not apply if there is a risk of rain. Do not apply when air or substrate temperatures are likely to fall below 8°C or above 25°C when the relative humidity is above 80% during application or the drying period.
PREPARATION	
General Timber Advice	Timber surfaces must be suitably prepared, clean, sound and dry. The moisture content should not exceed 18% prior to filling. All existing paint, woodstain or varnish must be totally removed from the area to be filled. All timber exhibiting signs of decay must be removed and cut back 25mm into sound material. When filling large areas consideration should be given to splicing in new timber sections. After cutting back, treat the area to be repaired (and any new timber) with Sadolin Quick Drying Wood Preserver or Sadolin Wood Preserver and allow to dry fully. Timber treated with Sadolin Quick Drying Wood Preserver can be repaired after 24 hours. When using Sadolin Wood Preserver , allow 72 hours drying time.
APPLICATION	<p>Sadolin Woodfiller is supplied ready for use. After storage a small amount of liquid may form on the surface of the material, this can easily be remixed into the material by stirring and does not affect performance.</p> <p>Always choose a colour of filler that is similar to the colour of the substrate (i.e., either that of the timber or of the stained timber). Alternatively choose Sadolin Stainable Woodfiller and use with your chosen woodstain or dye.</p> <p>The filler remains workable for up to 2 minutes at a temperature of 20°C. The material should be applied with a plastic spatula, filling knives or similar implement and left slightly 'proud' of the surface to allow for subsequent machining or sanding. Apply the filler carefully to ensure all air is displaced and good contact is made between the filler and the timber. Do not smear the filler around the area to be filled as this will affect the absorbency of the timber and may result in a poor visual appearance when subsequently stained or varnished. Consider using masking tape to protect surrounding areas if practical – remove whilst product is still workable.</p>



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG. Tel: 01254 704951

TECHNICAL DATA SHEET



	<p>Do not apply to holes greater than 5mm. For larger holes we recommend Sadolin Stainable Woodfiller.</p> <p>The filler can be sanded after approximately 30 minutes and coated after 2 hours. Carefully sand the filler flush to the timber surface using a medium grade abrasive paper. Remove all dust.</p>
OVERCOATING	<p>If the timber that is filled is much darker than the filler, or if the surrounding timber has been stained, apply a little stain to the filled surface using an artist's brush, to bring it to a similar colour before coating the whole surface. More permeable timbers will absorb stain to a greater extent than the filler and 2 or 3 applications of stain to the filled area may be needed to achieve the desired result.</p> <p>Always carry out a test application, especially when accurate colour matching is important. It is essential to ensure that the colour match between the substrate and filler is acceptable in terms of colour, density and workmanship before overcoating with clear or translucent finishing coats.</p>
CLEANING	<p>Return surplus material to container. Filling knives and other equipment should be cleaned with warm water before the product hardens.</p>
HEALTH AND SAFETY	<p>Please refer to the Safety, Health and Environmental Information on the container.</p> <p>Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. When preparing the surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask.</p> <p>Material Safety Data Sheets for this and all other Sadolin products are freely available from the place of purchase or the address below, or visit sadolin.co.uk</p> <p>Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.</p>
STORAGE	<p>Store upright and secure. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not store below 5°C or above 25°C.</p>
GENERAL INFORMATION	<p>Apply all products in accordance with:</p> <p>BS 6150: Code of practice for painting of buildings</p> <p>BS 8000: Part 12: Code of practice for decorative wallcoverings and painting</p> <p>BS EN 927-1: Coating materials and coating systems for exterior wood Part 1: Classification and selection.</p> <p>Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.</p> <p>Before using this product, please ensure you have the latest information. For help or more information contact the Sadolin Customer Relations Team on:</p> <p>Tel: 0330 024 0298</p> <p>Fax: 0330 0240278</p> <p>e-mail: info@sadolin.co.uk</p> <p>website: www.sadolin.co.uk</p> <p>This information is correct at date of issue December 2021.</p>



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG. Tel: 01254 704951

Crown Paints Ireland Ltd, Unit 8A, Coolmine Central, Porters Road, Coolmine Ind Est, Dublin 15, D15 AX9A. Tel: 00353 1 8164400