



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

# SAFETY DATA SHEET

## UNDERCOAT

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

GHS product identifier :  UNDERCOAT

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use :  Use in accordance with directions on the can.

#### 1.3. Details of the supplier of the safety data sheet

ICI Paints AkzoNobel,  
Wexham Road,  
Slough,  
Berkshire,  
SL2 5DS, U.K.  
Tel.: +44 (0) 333 222 70 70  
www.armsteadtrade.co.uk

e-mail address of person responsible for this SDS : armstead.advice@akzonobel.com

#### 1.4 Emergency telephone number

##### National advisory body/Poison Centre

Telephone number : +44 (0)344 892 0111

##### Supplier

Telephone number : T +44 (0) 1753 550000

Version : **2.02**

Date of previous issue : 6-6-2023

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms :



UNDERCOAT

SECTION 2: Hazards identification

- Signal word** : Warning
- Hazard statements** : H226 - Flammable liquid and vapour.
- Precautionary statements**
- General** : P102 - Keep out of reach of children.  
P101 - If medical advice is needed, have product container or label at hand.
- Prevention** : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Response** : Not applicable.
- Storage** : P403 + P235 - Store in a well-ventilated place. Keep cool.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.
- Supplemental label elements** : Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name                                             | Identifiers                                                   | %         | Classification                                                       | Specific Conc. Limits, M-factors and ATEs | Type    |
|---------------------------------------------------------------------|---------------------------------------------------------------|-----------|----------------------------------------------------------------------|-------------------------------------------|---------|
| titanium dioxide                                                    | REACH #: 01-2119489379-17<br>EC: 236-675-5<br>CAS: 13463-67-7 | ≥20 - ≤25 | Carc. 2, H351 (inhalation)                                           | -                                         | [1] [*] |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | REACH #: 01-2119463258-33<br>EC: 919-857-5                    | ≥10 - ≤15 | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>EUH066 | -                                         | [1]     |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics                | EC: 919-857-5<br>CAS: 64742-48-9                              | ≤4.7      | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>Asp. Tox. 1, H304           | -                                         | [1]     |
| Hydrocarbons,C10-C13,n-                                             | REACH #:                                                      | ≤3        | Asp. Tox. 1, H304                                                    | -                                         | [1]     |

**UNDERCOAT**

### SECTION 3: Composition/information on ingredients

|                                                                             |                                                                  |      |                 |   |     |
|-----------------------------------------------------------------------------|------------------------------------------------------------------|------|-----------------|---|-----|
| alkanes, isoalkanes, cyclics, <2% aromatics                                 | 01-2119457273-39<br>EC: 918-481-9                                |      | EUH066          |   |     |
| (2-methoxymethylethoxy) propanol                                            | REACH #:<br>01-2119450011-60<br>EC: 252-104-2<br>CAS: 34590-94-8 | ≤0.3 | Not classified. | - | [2] |
| propylidynetrimethanol                                                      | REACH #:<br>01-2119486799-10<br>EC: 201-074-9<br>CAS: 77-99-6    | ≤0.3 | Repr. 2, H361   | - | [1] |
| <b>See Section 16 for the full text of the H statements declared above.</b> |                                                                  |      |                 |   |     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

|                                   |                                                                                                                                                                                                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye contact</b>                | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.                           |
| <b>Inhalation</b>                 | : Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                                                                                                          |
| <b>Skin contact</b>               | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.                                                                                |
| <b>Ingestion</b>                  | : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. |
| <b>Protection of first-aiders</b> | : No action shall be taken involving any personal risk or without suitable training.                                                                                                                            |

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

 **UNDERCOAT**

## SECTION 4: First aid measures

### Over-exposure signs/symptoms

|              |                     |
|--------------|---------------------|
| Eye contact  | : No specific data. |
| Inhalation   | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion    | : No specific data. |

### 4.3 Indication of any immediate medical attention and special treatment needed

|                     |                                                                                                                             |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Notes to physician  | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment.                                                                                                    |

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

|                                |                                                                  |
|--------------------------------|------------------------------------------------------------------|
| Suitable extinguishing media   | : Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam. |
| Unsuitable extinguishing media | : Do not use water jet.                                          |

### 5.2 Special hazards arising from the substance or mixture

|                                       |                                                                                                                                                                                                                  |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazards from the substance or mixture | : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. |
| Hazardous combustion products         | : Decomposition products may include the following materials:<br>carbon dioxide<br>carbon monoxide<br>metal oxide/oxides                                                                                         |

### 5.3 Advice for firefighters

|                                                |                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Special protective actions for fire-fighters   | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.                                      |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

|                             |                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment. |
| For emergency responders    | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".                                                                                                                                           |

 **UNDERCOAT**

## SECTION 6: Accidental release measures

**6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8.2 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

| Category | Notification and MAPP threshold | Safety report threshold |
|----------|---------------------------------|-------------------------|
| P5c      | 5000 tonne                      | 50000 tonne             |

 **UNDERCOAT**

## SECTION 7: Handling and storage

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name         | Exposure limit values                                                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| (2-methoxymethylethoxy)propanol | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b><br>TWA: 308 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours. |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

| Product/ingredient name         | Type | Exposure             | Value                  | Population         | Effects  |
|---------------------------------|------|----------------------|------------------------|--------------------|----------|
| (2-methoxymethylethoxy)propanol | DNEL | Long term Oral       | 36 mg/kg bw/day        | General population | Systemic |
|                                 | DNEL | Long term Inhalation | 37.2 mg/m <sup>3</sup> | General population | Systemic |
|                                 | DNEL | Long term Dermal     | 121 mg/kg bw/day       | General population | Systemic |
|                                 | DNEL | Long term Dermal     | 283 mg/kg bw/day       | Workers            | Systemic |
|                                 | DNEL | Long term Inhalation | 308 mg/m <sup>3</sup>  | Workers            | Systemic |
| propylidynetrimethanol          | DNEL | Long term Oral       | 0.34 mg/kg bw/day      | General population | Systemic |
|                                 | DNEL | Long term Dermal     | 0.34 mg/kg bw/day      | General population | Systemic |
|                                 | DNEL | Long term Inhalation | 0.58 mg/m <sup>3</sup> | General population | Systemic |
|                                 | DNEL | Long term Dermal     | 0.94 mg/kg bw/day      | Workers            | Systemic |
|                                 | DNEL | Long term Inhalation | 3.3 mg/m <sup>3</sup>  | Workers            | Systemic |

#### PNECs

## SECTION 8: Exposure controls/personal protection

No PNECs available

### 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness  $\geq 0.38$  mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness  $\geq 0.12$  mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

UNDERCOAT

SECTION 8: Exposure controls/personal protection

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

**Physical state** : Liquid.  
**Colour** : Various: See label.  
**Odour** : Not available.  
**Odour threshold** : Not available.  
**Melting point/freezing point** : Not available.  
**Boiling point, initial boiling point, and boiling range** : 100°C (212°F)  
**Flammability** : Not available.  
**Lower and upper explosion limit** : Not available.  
**Flash point** : Closed cup: 32°C (89.6°F) [Pensky-Martens]  
**Auto-ignition temperature** :

| Ingredient name                                                                 | °C         | °F         | Method    |
|---------------------------------------------------------------------------------|------------|------------|-----------|
| (2-methoxymethylethoxy)propanol                                                 | 207        | 404.6      | EU A.15   |
| Distillates (petroleum), hydrotreated light                                     | >220       | >428       |           |
| 8,18-dichloro-5,15-diethyl-5,15-dihydrodiindolo[3,2-b:3',2'-m]triphenodioxazine | 250        | 482        |           |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics             | 280 to 470 | 536 to 878 |           |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics                            | 280 to 470 | 536 to 878 |           |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics            | 280 to 470 | 536 to 878 |           |
| Naphtha (petroleum), hydrotreated heavy                                         | 280 to 470 | 536 to 878 | EU A.15   |
| butan-1-ol                                                                      | 355        | 671        |           |
| 29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper                             | 356        | 672.8      | EU A.16   |
| ethylenediamine                                                                 | 405        | 761        | DIN 51794 |
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene                         | 432        | 809.6      |           |
| methanol                                                                        | 455        | 851        | DIN 51794 |

**Decomposition temperature** : Not available.  
**pH** : Not applicable. [DIN EN 1262]  
**Viscosity** : Kinematic: 505 mm<sup>2</sup>/s [DIN EN ISO 3219]  
**Solubility(ies)** :

| Media      | Result                      |
|------------|-----------------------------|
| cold water | Not soluble [OESO (TG 105)] |

UNDERCOAT

SECTION 9: Physical and chemical properties

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

| Ingredient name                                                     | Vapour Pressure at 20 °C |               |                | Vapour pressure at 50 °C |     |        |
|---------------------------------------------------------------------|--------------------------|---------------|----------------|--------------------------|-----|--------|
|                                                                     | mm Hg                    | kPa           | Method         | mm Hg                    | kPa | Method |
| methanol                                                            | 126.96                   | 16.9          | DIN EN 13016-2 |                          |     |        |
| water                                                               | 23.8                     | 3.2           |                |                          |     |        |
| ethylenediamine                                                     | 10.5                     | 1.4           |                |                          |     |        |
| butan-1-ol                                                          | <7.5                     | <1            |                |                          |     |        |
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene             | 6.7                      | 0.89          |                |                          |     |        |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | 0.75 to 2.25             | 0.1 to 0.3    |                |                          |     |        |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics                | 0.75 to 2.25             | 0.1 to 0.3    |                |                          |     |        |
| Hydrocarbons,C10-C13,n-alkanes, isoalkanes,cyclics,<2%aromatics     | 0.75 to 2.25             | 0.1 to 0.3    |                |                          |     |        |
| Naphtha (petroleum), hydrotreated heavy                             | 0.75 to 2.25             | 0.1 to 0.3    |                |                          |     |        |
| Distillates (petroleum), hydrotreated light                         | 0.23 to 0.45             | 0.031 to 0.06 |                |                          |     |        |
| propylidynetrimethanol                                              | 0                        | 0             | EU A.4         |                          |     |        |
| 29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper                 | 0                        | 0             |                |                          |     |        |

Relative density : 1.388  
Density : 1.388 g/cm³ [DIN EN ISO 2811-1]  
Vapour density : Not available.

Particle characteristics

Median particle size : Not applicable.  
Percentage of particles with aerodynamic diameter ≤ 10 µm : 0

SECTION 10: Stability and reactivity

- 10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability : The product is stable.
- 10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- 10.5 Incompatible materials : Reactive or incompatible with the following materials:  
oxidising materials

UNDERCOAT

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name                                             | Result                 | Species | Dose        | Exposure |
|---------------------------------------------------------------------|------------------------|---------|-------------|----------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | LC50 Inhalation Vapour | Rat     | 8500 mg/m³  | 4 hours  |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics                | LD50 Oral              | Rat     | >6 g/kg     | -        |
|                                                                     | LC50 Inhalation Vapour | Rat     | 8500 mg/m³  | 4 hours  |
| Hydrocarbons,C10-C13,n-alkanes,isoalkanes,cyclics, <2%aromatics     | LD50 Oral              | Rat     | >6 g/kg     | -        |
|                                                                     | LC50 Inhalation Vapour | Rat     | 8500 mg/m³  | 4 hours  |
| (2-methoxymethylethoxy) propanol<br>propylidynetrimethanol          | LD50 Oral              | Rat     | >6 g/kg     | -        |
|                                                                     | LD50 Oral              | Rat     | 5400 uL/kg  | -        |
|                                                                     | LD50 Oral              | Mouse   | 13700 mg/kg | -        |
|                                                                     | LD50 Oral              | Mouse   | 14000 mg/kg | -        |
|                                                                     | LD50 Oral              | Rat     | 14100 mg/kg | -        |
|                                                                     | LD50 Oral              | Rat     | 14000 mg/kg | -        |

Conclusion/Summary : Not available.

Acute toxicity estimates

N/A

Irritation/Corrosion

| Product/ingredient name          | Result               | Species | Score | Exposure          | Observation |
|----------------------------------|----------------------|---------|-------|-------------------|-------------|
| titanium dioxide                 | Skin - Mild irritant | Human   | -     | 72 hours 300 ug l | -           |
| (2-methoxymethylethoxy) propanol | Eyes - Mild irritant | Human   | -     | 8 mg              | -           |
|                                  | Eyes - Mild irritant | Rabbit  | -     | 24 hours 500 mg   | -           |
|                                  | Skin - Mild irritant | Rabbit  | -     | 500 mg            | -           |

Conclusion/Summary : Not available.

Sensitisation

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

 **UNDERCOAT**

## SECTION 11: Toxicological information

| Product/ingredient name                                             | Category   | Route of exposure | Target organs    |
|---------------------------------------------------------------------|------------|-------------------|------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | Category 3 | -                 | Narcotic effects |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics                | Category 3 | -                 | Narcotic effects |

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

| Product/ingredient name                                              | Result                         |
|----------------------------------------------------------------------|--------------------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  | ASPIRATION HAZARD - Category 1 |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics                 | ASPIRATION HAZARD - Category 1 |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | ASPIRATION HAZARD - Category 1 |

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.  
**Inhalation** : No specific data.  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.  
**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

UNDERCOAT

SECTION 11: Toxicological information

- 11.2 Information on other hazards
- 11.2.1 Endocrine disrupting properties
- Not available.
- 11.2.2 Other information
- Not available.

SECTION 12: Ecological information

- 12.1 Toxicity
- There are no data available on the mixture itself.
- Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

| Product/ingredient name | Result                                                                        | Species                                                 | Exposure             |
|-------------------------|-------------------------------------------------------------------------------|---------------------------------------------------------|----------------------|
| propylidynetrimethanol  | Acute EC50 13000000 µg/l Fresh water<br>Acute LC50 14400000 µg/l Marine water | Daphnia - Daphnia magna<br>Fish - Cyprinodon variegatus | 48 hours<br>96 hours |

Conclusion/Summary : Not available.

- 12.2 Persistence and degradability
- Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

| Product/ingredient name                                              | LogP <sub>ow</sub> | BCF        | Potential |
|----------------------------------------------------------------------|--------------------|------------|-----------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  | -                  | 10 to 2500 | high      |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics                 | -                  | 10 to 2500 | high      |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | -                  | 10 to 2500 | high      |
| (2-methoxymethylethoxy) propanol                                     | 0.004              | -          | low       |
| propylidynetrimethanol                                               | -0.47              | <1         | low       |

- 12.4 Mobility in soil
- Soil/water partition coefficient (K<sub>oc</sub>) : Not available.
- Mobility : Not available.

- 12.5 Results of PBT and vPvB assessment
- This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

- 12.6 Endocrine disrupting properties
- Not available.

- 12.7 Other adverse effects
- No known significant effects or critical hazards.

UNDERCOAT

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.
- Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

| Waste code    | Waste designation                                                                 |
|---------------|-----------------------------------------------------------------------------------|
| EWC 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

|                                 | ADR/RID | IMDG   |
|---------------------------------|---------|--------|
| 14.1 UN number                  | UN1263  | UN1263 |
| 14.2 UN proper shipping name    | PAINT   | PAINT  |
| 14.3 Transport hazard class(es) | 3       | 3      |
| 14.4 Packing group              | III     | III    |
|                                 |         |        |

 **UNDERCOAT**

## SECTION 14: Transport information

|                               |     |     |
|-------------------------------|-----|-----|
| 14.5<br>Environmental hazards | No. | No. |
|-------------------------------|-----|-----|

### Additional information

**ADR/RID** : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.  
**Tunnel code** (D/E)

**IMDG** : **Emergency schedules** F-E, S-E  
**Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

**14.6 Special precautions for user** : **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### UK (GB) /REACH

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : Not available.

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

 **UNDERCOAT**

**SECTION 15: Regulatory information**

**Persistent Organic Pollutants**  
Not listed.

**Seveso Directive**  
This product is controlled under the Seveso Directive.

|                               |
|-------------------------------|
| <b><u>Danger criteria</u></b> |
| <b>Category</b>               |
| P5c                           |

**International regulations**  
**Chemical Weapon Convention List Schedules I, II & III Chemicals**  
Not listed.

**Montreal Protocol**  
Not listed.

**Stockholm Convention on Persistent Organic Pollutants**  
Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)**  
Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals**  
Not listed.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

| Classification     | Justification         |
|--------------------|-----------------------|
| Flam. Liq. 3, H226 | On basis of test data |

**Full text of abbreviated H statements**

 UNDERCOAT

## SECTION 16: Other information

|        |                                                                    |
|--------|--------------------------------------------------------------------|
| H225   | Highly flammable liquid and vapour.                                |
| H226   | Flammable liquid and vapour.                                       |
| H301   | Toxic if swallowed.                                                |
| H302   | Harmful if swallowed.                                              |
| H304   | May be fatal if swallowed and enters airways.                      |
| H311   | Toxic in contact with skin.                                        |
| H312   | Harmful in contact with skin.                                      |
| H315   | Causes skin irritation.                                            |
| H318   | Causes serious eye damage.                                         |
| H319   | Causes serious eye irritation.                                     |
| H331   | Toxic if inhaled.                                                  |
| H332   | Harmful if inhaled.                                                |
| H335   | May cause respiratory irritation.                                  |
| H336   | May cause drowsiness or dizziness.                                 |
| H361   | Suspected of damaging fertility or the unborn child.               |
| H370   | Causes damage to organs.                                           |
| H372   | Causes damage to organs through prolonged or repeated exposure.    |
| H373   | May cause damage to organs through prolonged or repeated exposure. |
| H412   | Harmful to aquatic life with long lasting effects.                 |
| EUH066 | Repeated exposure may cause skin dryness or cracking.              |

### Full text of classifications [CLP/GHS]

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                     |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3                 |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                  |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                  |
| Flam. Liq. 2      | FLAMMABLE LIQUIDS - Category 2                                  |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                  |
| Repr. 2           | REPRODUCTIVE TOXICITY - Category 2                              |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| STOT RE 1         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT RE 2         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 1         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1   |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3   |

Date of printing : 20-6-2023

Date of issue/ Date of revision : 19-6-2023

Date of previous issue : 6-6-2023

Version : 2.02

### Notice to reader

**IMPORTANT NOTE** The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

 UNDERCOAT

**SECTION 16: Other information**

*writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.*

*Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.*

**Head Office**  
**AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands**