

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Osmo WR Base Coat 4001

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Wood preservatives

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf

Further information obtainable from:

Product safety department
 Phone: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
 Aquatic Acute 1 H400 Very toxic to aquatic life.
 Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS08 GHS09

Signal word

Danger

Hazard-determining components of labelling:

aliphatic hydrocarbons, C10-C13
 3-Iodo-2-propynylbutylcarbamate

Hazard statements

H304 May be fatal if swallowed and enters airways.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.

(Contd. on page 2)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 1)

Additional information:

P103 Read label before use.
P273 Avoid release to the environment.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P391 Collect spillage.
P405 Store locked up.
P501 Dispose of contents/container in accordance with national regulations.
Observe the general safety regulations when handling chemicals.
Always wear a dust mask when sanding.
EUH066 Repeated exposure may cause skin dryness or cracking.
Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39	aliphatic hydrocarbons, C10-C13 Asp. Tox. 1, H304	75-100%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<5%
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7 Reg.nr.: 01-2119489924-20	3-Iodo-2-propynylbutylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	0.1-<1%
CAS: 107534-96-3 ELINCS: 403-640-2 Index number: 603-197-00-7	1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol Acute Tox. 3, H331; Repr. 2, H361d; Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302	0.1-≤1%
CAS: 52645-53-1 EINECS: 258-067-9 Index number: 613-058-00-2	permethrin (ISO) Aquatic Acute 1, H400 (M=1000); Aquatic Chronic 1, H410 (M=1000); Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317	<0.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons out into the fresh air.

Keep warm, position comfortably and cover well.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Supply fresh air or oxygen; call for doctor.

Seek medical treatment in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

In case of skin reactions, seek medical advice.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

If swallowed, seek medical advice immediately and show this container or label.

Rinse mouth.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of if there is a fire.

No action shall be taken involving any personal risk or without suitable training.

Move container from fire area if it can be done without risk.

Use water spray to keep fire-exposed containers cool.

This material is very toxic to aquatic organisms.

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

(Contd. on page 4)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 3)

Protective equipment:

Wear self-contained respiratory protective device.
Fire-fighters should wear appropriate equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training.
Wear protective equipment. Keep unprotected persons away.
Do not touch or walk through spilt material.
Keep away from ignition sources.
Do not breathe vapour/spray.
Ensure adequate ventilation
Wear protective clothing.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Warm water and cleansing agent

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 1 for emergency contact information.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Information about fire - and explosion protection:

Protect from heat.
Protect against electrostatic charges.
Flammable gas-air mixtures may form in empty receptacles.
Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.
Store only in the original receptacle.

(Contd. on page 5)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 4)

Information about storage in one common storage facility:

Store away from foodstuffs.
 Store locked up.
 Store away from oxidising agents.

Further information about storage conditions:

Keep container tightly sealed.
 Protect from heat and direct sunlight.
 Store in cool, dry conditions in well sealed receptacles.

Storage class:

10

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

34590-94-8 Dipropylene glycol monomethyl ether

WEL	Long-term value: 308 mg/m ³ , 50 ppm
Sk	

Additional information:

The lists valid during the making were used as basis.
 Observe European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparisons with limit values and measurement strategy)
 Observe European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.)

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.
 Do not eat, drink, smoke or sniff while working.
 Immediately remove all soiled and contaminated clothing
 Do not carry product impregnated cleaning cloths in trouser pockets.
 Avoid contact with the eyes and skin.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.
 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
 Short term filter device:
 Full mask with type ABEK filter.

Protection of hands:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product

(Contd. on page 6)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 5)

is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

Nitrile rubber, NBR

PVC gloves

Penetration time of glove material Recommended thickness of the material: ≥ 4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Eye protection:

Recommended:

Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: Yellowish

Odour: Characteristic

Odour threshold: Not determined.

pH-value: Not determined.

Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

Flash point: 65 °C (EG A 9/DIN EN ISO 2719)

Flammability (solid, gas): Not applicable.

Ignition temperature: 225 °C

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

(Contd. on page 7)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 6)

Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	0.804 kg/l (DIN 51757)
Relative density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C:	1.7 mPa s
Kinematic at 20 °C:	0.02 cm²/s
9.2 Other information	Napięcie powierzchniowe: 25 mN/m (25 °C)

SECTION 10: Stability and reactivity

10.1 Reactivity	No further relevant information available.
10.2 Chemical stability	
Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
10.3 Possibility of hazardous reactions	No dangerous reactions known.
10.4 Conditions to avoid	Keep away from sources of ignition - No smoking. Avoid release to the environment.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition products:	No hazardous decomposition products when stored and handled correctly.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

(Contd. on page 8)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 7)

34590-94-8 Dipropylene glycol monomethyl ether		
Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rat) 13000 - 14000 mg/kg (rabbit)
Inhalative	LC50 / 4h	500 mg/l (rat)
	LC50 / 72h	0.76 mg/l (selenastrum capricornutum)
55406-53-6 3-Iodo-2-propynylbutylcarbamate		
Oral	LD50	1470 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4h	>6.89 mg/l (rat)
107534-96-3 1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol		
Oral	LD50	1700 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rat)
52645-53-1 permethrin (ISO)		
Oral	LD50	1479 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rat) > 4000 mg/kg (rabbit)
Inhalative	LC50 / 4h	> 0.599 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Acute effects (acute toxicity, irritation and corrosivity) May be fatal if swallowed and enters airways.

Sensitisation Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

(Contd. on page 9)

Trade name: Osmo WR Base Coat 4001

(Contd. of page 8)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

aliphatic hydrocarbons, C10-C13

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)
Biolog. Abbaubarkeit	(leicht abbaubar)

34590-94-8 Dipropylene glycol monomethyl ether

EC50 / 48h (Static)	1919 mg/l (daphnia)
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
LC50 / 48h	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50 / 48h	0.16 mg/l (daphnia)
EC50/ 72h	0.022 mg/l (algae)

107534-96-3 1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol

EC50 / 48h	2.79 mg/l (daphnia)
IC50/ 3h	4 mg/l (algae)
LC50 / 96h	4.4 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

52645-53-1 permethrin (ISO)

IC50/ 3h	0.17 mg/l (daphnia)
LC50 / 96h	0.0076 mg/l (Poecilia reticulata)

12.2 Persistence and degradability The solvent is biodegradable.

A part of the components is heavily biodegradable.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Very toxic for fish

Behaviour in sewage processing plants:

55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50/ 96h	0.067 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
-----------	--

107534-96-3 1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol

EC10	1890 mg/l (Bakterientoxizität)
------	--------------------------------

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 10)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 9)

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

03 02 02*	organochlorinated wood preservatives
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information**14.1 UN-Number**

ADR, IMDG, IATA UN3082

14.2 UN proper shipping name

ADR 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PERMETHRIN)
IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PERMETHRIN), MARINE POLLUTANT
IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PERMETHRIN)

14.3 Transport hazard class(es)**ADR**

Class 9 (M6) Miscellaneous dangerous substances and articles.

Label 9

IMDG, IATA

Class 9 Miscellaneous dangerous substances and articles.

Label 9

(Contd. on page 11)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 10)

14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant: Special marking (ADR): Special marking (IATA):	Product contains environmentally hazardous substances: 3-Iodo-2-propynylbutylcarbamate, permethrin (ISO) Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PERMETHRIN), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances -

ANNEX I

None of the ingredients is listed.

Seveso category

E1 Hazardous to the Aquatic Environment

(Contd. on page 12)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 11)

*Qualifying quantity (tonnes) for
the application of lower-tier
requirements*

100 t

*Qualifying quantity (tonnes) for
the application of upper-tier
requirements*

200 t

National regulations:

Marking in accordance with biocide guideline 98/8/EG

55406-53-6	3-Iodo-2-propynylbutylcarbamate	5.01 g/kg
107534-96-3	1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol	2.02 g/kg
52645-53-1	permethrin (ISO)	0.6 g/kg

*Regulation (EC) No 648/2004 on
detergents*

HSE: 10169

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H361d Suspected of damaging the unborn child.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

Department issuing SDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 13)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 11.05.2018

Trade name: Osmo WR Base Coat 4001

(Contd. of page 12)

Acute Tox. 3: Acute toxicity – Category 3

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1