

TECHNICAL DATA SHEET

TDS 1829 AC/EGG 12/23 V7



VINTAGE COLOURS

ACRYLIC EGGSHELL

TYPE OF MATERIAL	A water based eggshell paint based on a pure Acrylic Emulsion resin with Titanium Dioxide and other selected pigments and Extenders.		
USES	A hardwearing washable eggshell sheen paint for woodwork and other surfaces receiving heavy wear. Can be used internally or on exterior wood and primed metal surfaces. It is tougher and has better adhesion than vinyl silk emulsion, but without the solvent fumes of oil based eggshell paints.		
COLOURS AVAILABLE	110 Vintage Colours – see website and shade card		
FINISH	EGGSHELL		
NUMBER OF COMPONENTS	One	MIXING RATIO	N/A
METHOD OF APPLICATION	Brush or Roller – can be sprayed		
AVAILABLE PACKS	750ml, 1Ltr & 2.5Ltr		
SHEEN LEVEL	Approx 16 - 24 Sheen @ 60°		
PRACTICAL COVERAGE PER LITRE	10-12 sq M / L, (7-9 sq M / 750 ML)		
WET FILM THICKNESS RANGE	60 – 75 microns		
DRY FILM THICKNESS RANGE	20– 25 microns		
FLASH POINT	N/A Water based.		
DRYING TIMES: SURFACE HARD OVERCOATING	1-2 Hours 2-4 Hours 4 Hours		
APPLICATION INSTRUCTIONS	Apply 2 coats by brush or roller (synthetic bristle brushes give good results). Previously painted gloss or lustre surfaces should be abraded to improve adhesion. See can for further details. Bare wood or plaster surfaces should be primed with Craig & Rose Primer Undercoat for best results. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood or metal as they may contain harmful lead. For further advice, please contact the British Coatings Federation Ltd, James House, Bridge Street, Leatherhead. KT22 7EP.		

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

VINTAGE COLOURS

ACRYLIC EGGSHELL

RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS	Ensure the previous coat is completely dry before over coating. Do not apply in temperatures near freezing as this will seriously slow down the drying and may destroy the structure of the paint. Store in a frost-free place and do not allow the paint to freeze.
CLEANING	Remove as much paint as possible from equipment before cleaning with water. Clean hands with warm soapy water.
SAFETY PRECAUTIONS	Ensure good ventilation during application and drying. After contact with skin, wash immediately with plenty of soap and water. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. See can label for full instructions. Safety Data Sheets are available on request.
VOC CONTENT (VOLATILE ORGANIC COMPOUNDS)	2004/42 EU Limit value for this product (Cat A/a :30 g/L) This product contains Max : 1.5g/L VOC.
DISPOSAL & ENVIRONMENT	Please dispose of unused paint and container responsibly. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of paint.

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.