

TECHNICAL DATA SHEET

TDS 1829 CHE 12/23 V6



VINTAGE COLOURS

CHALKY EMULSION

TYPE OF MATERIAL	A Water based Chalky Matt finish made with Acrylic Emulsion, Titanium Dioxide and other selected Extenders and Pigments. Specially enhanced to give better wash and rub resistance than normal flat wall paints with an especially low sheen matt finish.		
USES	A high quality low sheen finish for interior walls and ceilings		
COLOURS AVAILABLE	110 Vintage Colours – see website and shade card		
FINISH	MATT		
NUMBER OF COMPONENTS	One	MIXING RATIO	N/A
METHOD OF APPLICATION	Brush or Roller – can be sprayed		
AVAILABLE PACKS	50ml Sample, 750ml, 2.5Ltr & 5.0Ltr		
SHEEN LEVEL	A true Matt 3 < @20°, 5 < @ 60°, 8 < @ 85°		
PRACTICAL COVERAGE PER LITRE	14sq M / L (35 sq M / 2.5 L.)		
WET FILM THICKNESS RANGE	65 – 80 microns		
DRY FILM THICKNESS RANGE	20 – 30 microns		
FLASH POINT	N/A Water based.		
DRYING TIMES: SURFACE HARD OVERCOATING	1-2 Hours 2-4 Hours 4 Hours		
APPLICATION INSTRUCTIONS	Apply 2 coats by brush or roller. New dry plaster surfaces should be primed with a coat of Craig & Rose Primer Undercoat or other suitable wall primer. Chalky emulsion paint can be thinned slightly with 5-10% of clean water to counteract any excessive suction when being used directly on to plaster surfaces. See can for further details. If using packs with different batch numbers then blend before use.		
RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS	Ensure the previous coat is completely dry before over coating. Do not apply in temperatures near freezing as this will seriously slow down the drying and may destroy the structure of the paint. Store in a frost-free place and do not allow the paint to freeze.		

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

VINTAGE COLOURS

CHALKY EMULSION

CLEANING	Remove as much paint as possible from equipment before cleaning with water. Clean hands with warm soapy water.
SAFETY PRECAUTIONS	Ensure good ventilation during application and drying. After contact with skin, wash immediately with plenty of soap and water. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. See can label for full instructions. Safety Data Sheets are available on request.
VOC CONTENT (VOLATILE ORGANIC COMPOUNDS)	2004/42 EU Limit value for this product (Cat A/a :30g/L) This product contains Max : 1.5g/L VOC.
DISPOSAL & ENVIRONMENT	Please dispose of unused paint and container responsibly. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of paint.

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.