

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 10.07.2018

Version number 4

Revision: 10.07.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Osmo Door Oil

Article number: 3060 Clear, 3033 Raw

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture No further relevant information available.

Application of the substance / the mixture Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf

Further information obtainable from:

Product safety department
 Phone: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Precautionary statements Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

P262 Do not get in eyes, on skin, or on clothing.

P271 Use only outdoors or in a well-ventilated area.

Additional information: Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 2)

Trade name: Osmo Door Oil


(Contd. of page 1)

2.3 Other hazards

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

| | | | |
|---|---------------------------------|---|--------|
| EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39 | aliphatic hydrocarbons, C10-C13 |  Asp. Tox. 1, H304 | 25-50% |
| CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17 | titanium dioxide | | 0-1% |

Additional information: The content of Titanium dioxide varies according to the colour shade.
For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Immediately remove any clothing soiled by the product.**After inhalation:** Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:** If swallowed, seek medical advice immediately and show this container or label.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 3)

Trade name: Osmo Door Oil

(Contd. of page 2)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles:

Store in a cool location.

(Contd. on page 4)

Trade name: Osmo Door Oil

(Contd. of page 3)

Information about storage in one common storage facility: Store only in the original receptacle.
Do not store together with alkalis (caustic solutions).
Do not store together with oxidising and acidic materials.

Further information about storage conditions: Keep container tightly sealed.
Store receptacle in a well ventilated area.
Protect from frost.
Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

aliphatic hydrocarbons, C10-C13

| | |
|-----------|--|
| TWA (8 H) | Long-term value: 1,000 mg/m ³ , 150 ppm ppm Source: UK SIA |
|-----------|--|

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.

Protection of hands:

Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

Goggles recommended during refilling

(Contd. on page 5)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 10.07.2018

Version number 4

Revision: 10.07.2018

Trade name: Osmo Door Oil**Body protection:** Protective work clothing

(Contd. of page 4)

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

| | |
|----------------|------------------------------------|
| Form: | Fluid |
| Colour: | According to product specification |
| Odour: | Mild |

Change in condition

| | |
|---|---------------|
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | Undetermined. |

Flash point: > 60 °C (DIN 52231)**Ignition temperature:** 240 °C**Auto-ignition temperature:** Product is not selfigniting.**Explosive properties:** Product does not present an explosion hazard.**Explosion limits:**

| | |
|---------------|-----------|
| Lower: | 0.6 Vol % |
| Upper: | 7.0 Vol % |

Vapour pressure: 3 hPa [20°C]**Density at 20 °C:** 0.90 - 1.0 g/cm³ (DIN 51757)**Solubility in / Miscibility with water:** Not miscible or difficult to mix.**Viscosity:**

| | |
|----------------------------|---------------------|
| Dynamic: | Not determined. |
| Kinematic at 20 °C: | >81 s (DIN 53211/4) |

Solvent content:**VOC (EC)** < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)**9.2 Other information** No further relevant information available.**SECTION 10: Stability and reactivity****10.1 Reactivity** No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.

(Contd. on page 6)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 10.07.2018

Version number 4

Revision: 10.07.2018

Trade name: Osmo Door Oil

(Contd. of page 5)

10.3 Possibility of hazardous reactions

Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NO_x)**Additional information:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**aliphatic hydrocarbons, C10-C13**

| | | |
|------------|-----------|-------------------------------|
| Oral | LD50 | >5,000 mg/kg (rat) (OECD 401) |
| Dermal | LD50 | >5,000 mg/kg (rat) (OECD 402) |
| Inhalative | LC50 / 4h | 21 mg/l (rat) (OECD 403) |

13463-67-7 titanium dioxide

| | | |
|--------|------|------------------------|
| Oral | LD50 | >20,000 mg/kg (rat) |
| Dermal | LD50 | >10,000 mg/kg (rabbit) |

Primary irritant effect:**Skin corrosion/irritation**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

(Contd. on page 7)

Trade name: Osmo Door Oil

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

aliphatic hydrocarbons, C10-C13

| | |
|----------------------|----------------------------------|
| EC50 / 48h | >1,000 mg/l (daphnia) (OECD 202) |
| EC50/ 72h | >1,000 mg/l (algae) (OECD 201) |
| LC50 / 96h | >1,000 mg/l (fish) (OECD 203) |
| Biolog. Abbaubarkeit | % (leicht abbaubar) |

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

| | |
|----------|---|
| 08 01 11 | waste paint and varnish containing organic solvents or other dangerous substances |
| 15 01 10 | packaging containing residues of or contaminated by dangerous substances |

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

(Contd. on page 8)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 10.07.2018

Version number 4

Revision: 10.07.2018

Trade name: Osmo Door Oil

(Contd. of page 7)

| | |
|--|-----------------|
| 14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class | Void |
| 14.4 Packing group ADR, IMDG, IATA | Void |
| 14.5 Environmental hazards: Marine pollutant: | No |
| 14.6 Special precautions for user | Not applicable. |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| UN "Model Regulation": | Void |

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations:**

VOC (EC) < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

| | |
|------------------------------------|--|
| Relevant phrases | H304 May be fatal if swallowed and enters airways. |
| Department issuing SDS: | product safety department |
| Contact: | Hr. Dr. Starp |
| Abbreviations and acronyms: | ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Asp. Tox. 1: Aspiration hazard – Category 1 |

(Contd. on page 9)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 10.07.2018

Version number 4

Revision: 10.07.2018

Trade name: Osmo Door Oil

** Data compared to the previous
version altered.*

(Contd. of page 8)