

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 6

Revision: 23.05.2018

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1 Product identifier**

**Trade name:** **Osmo Hardwax-Oil Anti-Slip**

**Article number:** 3088, 3089

### **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

### **Application of the substance / the mixture**

Coating compound/ Surface coating/ paint  
 Paint

### **1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
 Affhüppen Esch 12  
 D-48231 Warendorf

### **Further information obtainable from:**

Product safety department  
 Phone: +49 (0) 251 / 692 - 188  
 Fax: +49 (0) 251 / 692 - 462  
 e-mail: helmut.starp@osmo.de

### **1.4 Emergency telephone number:**

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

## **SECTION 2: Hazards identification**

### **2.1 Classification of the substance or mixture**

#### **Classification according to**

**Regulation (EC) No 1272/2008** The product is not classified, according to the CLP regulation.

### **2.2 Label elements**

#### **Labelling according to Regulation**

**(EC) No 1272/2008** Void

**Hazard pictograms** Void

**Signal word** Void

**Hazard statements** Void

**Precautionary statements** Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing.

P271 Use only outdoors or in a well-ventilated area.

**Additional information:** Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

Safety data sheet available on request.

(Contd. on page 2)

**Material Safety Data Sheets**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 6

Revision: 23.05.2018

**Trade name: Osmo Hardwax-Oil Anti-Slip**

(Contd. of page 1)

**2.3 Other hazards**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

|                            |                                 |                                                                                                       |        |
|----------------------------|---------------------------------|-------------------------------------------------------------------------------------------------------|--------|
| EC number: 918-481-9       | aliphatic hydrocarbons, C10-C13 |  Asp. Tox. 1, H304 | 25-50% |
| Index number: 649-327-00-6 |                                 |                                                                                                       |        |
| Reg.nr.: 01-2119457273-39  |                                 |                                                                                                       |        |

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures****General information:**

Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

**After inhalation:**

Supply fresh air; consult doctor in case of complaints.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:**

If swallowed, seek medical advice immediately and show this container or label.

**4.2 Most important symptoms and effects, both acute and delayed**

Dizziness

Headache

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media****Suitable extinguishing agents:**CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

**5.3 Advice for firefighters****Protective equipment:**

No special measures required.

(Contd. on page 3)

**Material Safety Data Sheets**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 6

Revision: 23.05.2018

**Trade name: Osmo Hardwax-Oil Anti-Slip**

(Contd. of page 2)

**Additional information**

Cool endangered receptacles with water spray.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### **SECTION 6: Accidental release measures**

**6.1 Personal precautions,  
protective equipment and  
emergency procedures**

Ensure adequate ventilation  
Keep away from ignition sources.

**6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for  
containment and cleaning up:**

Warm water and cleansing agent  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

**6.4 Reference to other sections**

No dangerous substances are released.

### **SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

Use only in well ventilated areas.  
Keep receptacles tightly sealed.  
No special measures required.

**Information about fire - and  
explosion protection:**

No special measures required.

**7.2 Conditions for safe storage, including any incompatibilities**  
**Storage:**

**Requirements to be met by**

**storerooms and receptacles:** Store only in the original receptacle.

**Information about storage in one  
common storage facility:**

Not required.

**Further information about  
storage conditions:**

None.

**7.3 Specific end use(s)**

No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

**Additional information about  
design of technical facilities:**

No further data; see item 7.

(Contd. on page 4)

**Material Safety Data Sheets**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 6

Revision: 23.05.2018

**Trade name: Osmo Hardwax-Oil Anti-Slip**

(Contd. of page 3)

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**aliphatic hydrocarbons, C10-C13**

|           |                                                                          |
|-----------|--------------------------------------------------------------------------|
| TWA (8 H) | Long-term value: 1.000 mg/m <sup>3</sup> , 150 ppm ppm<br>Source: UK SIA |
|-----------|--------------------------------------------------------------------------|

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.  
Do not carry product impregnated cleaning cloths in trouser pockets.  
Avoid contact with the eyes and skin.

**Respiratory protection:**

Use suitable respiratory protective device only when aerosol or mist is formed.  
Not necessary if room is well-ventilated.  
Short term filter device:

**Protection of hands:**

Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 ° C)).  
To avoid skin problems reduce the wearing of gloves to the required minimum.  
Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**Eye protection:**

Goggles recommended during refilling

**Body protection:**

Protective work clothing

(Contd. on page 5)

**Material Safety Data Sheets**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 6

Revision: 23.05.2018

**Trade name: Osmo Hardwax-Oil Anti-Slip**

(Contd. of page 4)

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### General Information

##### Appearance:

|                |           |
|----------------|-----------|
| <b>Form:</b>   | Viscous   |
| <b>Colour:</b> | Yellowish |
| <b>Odour:</b>  | Mild      |

##### Change in condition

|                                                 |               |
|-------------------------------------------------|---------------|
| <b>Melting point/freezing point:</b>            | Undetermined. |
| <b>Initial boiling point and boiling range:</b> | > 144 °C      |

**Flash point:** > 61 °C (DIN EN ISO 2719)

**Ignition temperature:** 240 °C

**Auto-ignition temperature:** Product is not selfigniting.

**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

##### Explosion limits:

|               |           |
|---------------|-----------|
| <b>Lower:</b> | 0.7 Vol % |
| <b>Upper:</b> | 6.0 Vol % |

**Vapour pressure at 20 °C:** 1 hPa

**Density at 20 °C:** 0.90-0.95 g/cm<sup>3</sup> (DIN 51757)

**Solubility in / Miscibility with water:** Not miscible or difficult to mix.

##### Viscosity:

|                            |                         |
|----------------------------|-------------------------|
| <b>Dynamic:</b>            | Not determined.         |
| <b>Kinematic at 20 °C:</b> | 30-34 s (DIN 53211/4mm) |

##### Solvent content:

**VOC (EC)** < 500 g/l (VOC-max. Cat A/i (2010) = 500 g/l)

**9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

#### 10.2 Chemical stability

**Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions**

Reacts with fabric soaked in the product (e.g. cleaning wool).

(Contd. on page 6)

**Material Safety Data Sheets**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 6

Revision: 23.05.2018

**Trade name: Osmo Hardwax-Oil Anti-Slip**

(Contd. of page 5)

**10.4 Conditions to avoid**

No further relevant information available.

**10.5 Incompatible materials:**

No further relevant information available.

**10.6 Hazardous decomposition products:**Carbon monoxide and carbon dioxide  
Nitrogen oxides (NO<sub>x</sub>)**Additional information:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

## SECTION 11: Toxicological information

**11.1 Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:****aliphatic hydrocarbons, C10-C13**

|            |           |                               |
|------------|-----------|-------------------------------|
| Oral       | LD50      | > 5000 mg/kg (rat) (OECD 401) |
| Dermal     | LD50      | > 5000 mg/kg (rat) (OECD 402) |
| Inhalative | LC50 / 4h | 21 mg/l (rat) (OECD 403)      |

**Primary irritant effect:****Skin corrosion/irritation**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

**Serious eye damage/irritation**

Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

**Carcinogenicity**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

**12.1 Toxicity****Aquatic toxicity:****aliphatic hydrocarbons, C10-C13**

|                      |                                  |
|----------------------|----------------------------------|
| EC50 / 48h           | > 1000 mg/l (daphnia) (OECD 202) |
| EC50/ 72h            | > 1000 mg/l (algae) (OECD 201)   |
| LC50 / 96h           | > 1000 mg/l (fish) (OECD 203)    |
| Biolog. Abbaubarkeit | (leicht abbaubar)                |

**12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 7)

**Material Safety Data Sheets**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 6

Revision: 23.05.2018

**Trade name: Osmo Hardwax-Oil Anti-Slip**

(Contd. of page 6)

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**Additional ecological information:**

**General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

**12.5 Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**European waste catalogue**

|           |                                                                                   |
|-----------|-----------------------------------------------------------------------------------|
| 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances |
| 15 01 10* | packaging containing residues of or contaminated by dangerous substances          |

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

**14.1 UN-Number**

**ADR, ADN, IMDG, IATA** Void

**14.2 UN proper shipping name**

**ADR, ADN, IMDG, IATA** Void

**14.3 Transport hazard class(es)**

**ADR, ADN, IMDG, IATA**

**Class** Void

**14.4 Packing group**

**ADR, IMDG, IATA** Void

**14.5 Environmental hazards:**

**Marine pollutant:** No

**14.6 Special precautions for user**

Not applicable.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

(Contd. on page 8)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 6

Revision: 23.05.2018

**Trade name: Osmo Hardwax-Oil Anti-Slip**

(Contd. of page 7)

UN "Model Regulation":

Void

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulations:

GISBAU-Code

GISCODE: Ö60

VOC (EC)

&lt; 500 g/l (VOC-max. = 500 g/l (2010 A/i))

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H304 May be fatal if swallowed and enters airways.

#### Department issuing SDS:

product safety department

#### Contact:

Hr. Dr. Starp

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Asp. Tox. 1: Aspiration hazard – Category 1

**\* Data compared to the previous version altered.**