

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Polyx®-Oil Rapid

Article number: 3232 Clear satin; 3240 White transparent; 3262 Clear matt

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Paint
Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf
Germany

Further information obtainable from:

Product safety department
Tel.: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

2.2 Label elements

Hazard pictograms



GHS02

Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat. - No smoking.
P262 Do not get in eyes, on skin, or on clothing.
P271 Use only outdoors or in a well-ventilated area.
P501 Dispose of contents/container in accordance with national regulations.
Additional information: 3240: EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH210 Safety data sheet available on request.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 1)

2.3 Other hazards

Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

Must not be applied on the same spraying stand as lacquers or lacquer corrosives that contain NC (nitrocellulose). Risk of self-ignition.

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

EC number: 918-481-9	aliphatic hydrocarbons, C10-C13 ⚠ Asp. Tox. 1, H304, EUH066	30–50%
EC number: 927-241-2	aliphatic hydrocarbons, C9-C10 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; Aquatic Chronic 3, H412	≥10–<20%
CAS: 34590-94-8 EINECS: 252-104-2	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<2.5%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide - aerodynamic dia meter >10 µm	0-2.5%

Additional information:

The content of Titanium dioxide varies according to the colour shade.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:** Take affected persons out into the fresh air.**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.**After swallowing:** If swallowed, seek medical advice immediately and show this container or label.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 2)

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

agents:

CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

No special measures required.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 3)

6.4 Reference to other sections

Do not flush with water or aqueous cleansing agents

See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas.
 Keep away from heat and direct sunlight.
 Keep receptacles tightly sealed.
 Prevent formation of aerosols.
 Open and handle receptacle with care.

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Store protective clothing separately.
 Do not inhale gases / fumes / aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.
 Store in a cool location.

Information about storage in one common storage facility:

Not required.

Further information about
storage conditions:

Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.

Storage class:

3

7.3 Specific end use(s)

No further relevant information available.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

aliphatic hydrocarbons, C10-C13

TWA	Short-term value: 1200 mg/m ³ CEFIC-HSPA
-----	--

34590-94-8 Dipropylene glycol monomethyl ether

IOELV	Long-term value: 308 mg/m ³ , 50 ppm Skin
-------	---

PNECs

34590-94-8 Dipropylene glycol monomethyl ether

PNEC sea water	190 mg/l
PNEC fresh water	19 mg/l
PNEC sewage treatment plant	4,168 mg/l
PNEC fresh water	19 mg/l
PNEC Sediment fresh water	70.2 mg/kg
PNEC STP	4,168 mg/l
PNEC Sediment marine water	190 mg/kg

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls

No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.
Keep away from foodstuffs, beverages and feed.
Avoid contact with the eyes and skin.
Immediately remove all soiled and contaminated clothing
Store protective clothing separately.
Do not inhale gases / fumes / aerosols.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.
Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.
Not necessary if room is well-ventilated.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 5)

Hand protection

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye/face protection

Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Physical state**

Fluid

Colour:

According to product specification

Odour:

Mild

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

> 144 °C

Lower and upper explosion limit**Lower:**

0.7 Vol %

Upper:

6.0 Vol %

Flash point:

45-52 °C (DIN EN ISO 2719)

Auto-ignition temperature:

Product is not selfigniting.

pH

Not applicable

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 6)

Viscosity:**Kinematic viscosity at 20 °C**

25-45 s (DIN EN ISO 2431/4mm)

>21 mm²/s (40°C) (calculated)**Dynamic:**

Not determined.

Solubility**water:**

Not miscible or difficult to mix.

Vapour pressure at 20 °C:

10 hPa

Density and/or relative density**Density at 20 °C:**0.88-0.95 g/cm³ (DIN 51757)**9.2 Other information****Appearance:****Form:**

Fluid

Important information on protection of health and environment, and on safety.**Ignition temperature:**

240 °C

Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Solvent content:**VOC (EC)**

< 500 g/l (VOC-max. Cat A/i (2010) = 500 g/l)

Information with regard to physical hazard classes**Explosives**

Void

Flammable gases

Void

Aerosols

Void

Oxidising gases

Void

Gases under pressure

Void

Flammable liquids

Flammable liquid and vapour.

Flammable solids

Void

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 7)

Self-reactive substances and mixtures**Pyrophoric liquids** Void**Pyrophoric solids** Void**Self-heating substances and mixtures** Void**Substances and mixtures, which emit flammable
gases in contact with water** Void**Oxidising liquids** Void**Oxidising solids** Void**Organic peroxides** Void**Corrosive to metals** Void**Desensitised explosives** Void

Void

SECTION 10: Stability and reactivity**10.1 Reactivity**

No further relevant information available.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 8)

10.2 Chemical stability**Thermal decomposition /****conditions to be avoided:**

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous**decomposition products:**Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)**Additional information:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute toxicity**

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**aliphatic hydrocarbons, C10-C13**

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

aliphatic hydrocarbons, C9-C10

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50 / 4h	>20 mg/l (rat)

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>19,020 mg/kg (rat) 13,000–14,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1,667 mg/l (rat)
	LC50 / 72h	0.76 mg/l (selenastrum capricornutum)

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin**sensitisation**

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 9)

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards
Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity:
aliphatic hydrocarbons, C10-C13

EC50 / 48h >1,000 mg/l (Daphnia magna)

IC50 / 72h >1,000 mg/l (algae)

LC50 / 96h >1,000 mg/l (fish)

aliphatic hydrocarbons, C9-C10

EC50 / 24h <130 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

>100 mg/l (selenastrum capricornutum)

34590-94-8 Dipropylene glycol monomethyl ether

EC50 / 48h 70.2 mg/l

1,919 mg/l (Daphnia magna)

LC50 / 96h 5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

LC50 / 48h 10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

12.2 Persistence and
degradability

No further relevant information available.

12.3 Bioaccumulative
potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment
PBT:

Not applicable.

vPvB:

Not applicable.

12.6 Endocrine disrupting
properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects
Additional ecological information:
General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 10)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

ADR 1263 PAINT
IMDG, IATA PAINT

14.3 Transport hazard class(es)

ADR
Class 3 (F1) Flammable liquids.
Label 3

IMDG, IATA

Class 3 Flammable liquids.
Label 3

14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Warning: Flammable liquids.
Hazard identification number (Kemler code): 30
EMS Number: F-E,S-E
Stowage Category A

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 11)

Transport/Additional information:
ADR
Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category

3

Tunnel restriction code

D/E

IMDG
Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Directive 2012/18/EU
Named dangerous
substances - ANNEX I

None of the ingredients is listed.

Seveso category

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes)
for the application of lower-
tier requirements

5,000 t

Qualifying quantity (tonnes)
for the application of upper-
tier requirements

50,000 t

REGULATION (EC) No
1907/2006 ANNEX XVII

Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148
Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 12)

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:
GISBAU-Code

GISCODE: Ö60

VOC (EC)

< 500 g/l (VOC-max. = 500 g/l (2010 A/i))

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Reasons for alterations

Formal Changes

Relevant phrases

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing SDS:

product safety department

Contact:

Hr. Dr. Starp

Version number of previous
version:

15.4

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route
 (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid**Sources**

Safety data sheets from raw material suppliers
ECHA Portal
ESIS : European chemical Substances Information System

(Contd. of page 13)

EU