



BEDEC PRODUCTS LTD.

Surface Coating Specialists

UNITS 1 & 2, POPLARS FARM, AYTHORPE RODING, DUNMOW, ESSEX CM6 1RY
TEL: 01279 876 657 FAX: 01279 876 008 email: info@bedec.co.uk Web site www.bedec.co.uk
VAT No. GB 432114990

BARN PAINT

*Acrylic

*Water-Based

*Semi-Gloss, Satin & Matt

Description

Bedec Barn Paint is ideally suited to the protection of exterior buildings such as barns, stables, outbuildings, sheds, silos, windmills, and factory units (corrugated and metal box cladding). It is highly recommended to coat, fencing, gates, farm equipment, tanks, drainpipes, doors, windows and many other areas around gardens, farms and factories. It can be applied to previously painted surfaces, even those coated with weathered bitumen, tar varnish or creosote. This acrylic system is a tough durable microporous protective coating with excellent colour retention. It will flex with the substrate exhibiting reduced flaking and blistering. Two or three coats can be applied quickly within one day, especially during the summer months. The advantage over conventional systems is that the coats applied are all Barn Paint, therefore no stress is built up within the coating layers. No need to etch or pre prime galvanised steel. Prime bare steel or rusty surfaces with an anti-corrosive metal primer.

Directions for Use

Stir thoroughly, check colour before use. Apply by brush roller or spray (use HVLP or Airless spray for best results). Do not apply at temperatures below 10°C or when foggy or likely to rain before the paint has dried. Ensure all surfaces are free from oil, grease, dirt, dust and loose particles. On existing painted surfaces, remove all loose and flaking paint and thoroughly rub down with abrasive paper. Any new finished wood needs to be abraded. On untreated, weathered wood, new wood, cement, render etc. or any porous substrate the first coat should be thinned with 30-40% clean water, followed by 2 or 3 unthinned coats to achieve maximum durability. Some surfaces are liable to have water solubles or wood treatments which can cause staining and loss of adhesion especially with white and lighter colours. Substrates to be careful of are some plywoods, red cedar wood, very resinous timber or damp walls. Test areas liable to staining and seal with Bedec Stain Block. Denatured wood needs to be abraded to remove loose material and expose new cells. Not recommended for pressure treated timber.

Coverage

Approx. 13-15 square metres per litre per coat depending upon substrate texture, porosity and application method. Spraying can reduce coverage rates to between 6 and 8 sq metres per litre.

Drying

Touch dry 2 hours, recoatable after 4 hours at 18°C 65% relative humidity.

Storage: Replace lid firmly, protect from low temperatures. Transport in a secure and upright position.

Flash Point: Not applicable.

Clean up: Warm soapy water.

Colour Range: see colour card

Health & Safety: Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water. After contact with skin, wash immediately with soap and water. Ensure good ventilation during application and drying.

Pack sizes: 2.5litres 5litres 20litres



BEDEC PRODUCTS LTD.

Surface Coating Specialists

UNITS 1 & 2, POPLARS FARM, AYTHORPE RODING, DUNMOW, ESSEX CM6 1RY
TEL: 01279 876 657 FAX: 01279 876 008 email: info@bedec.co.uk Web site www.bedec.co.uk
VAT No. GB 432114990

COSHH data sheets available on request.